



SUPER EVAC PUMP 95 l/min.



Non-contractual photo.

OVERVIEW

Two-stage vacuum pump for optimum drainage of all commercial refrigerator and air-conditioning refrigeration systems.

Sturdy, made of resistant metal and with electrical protection built into the motor, the pump is silent and comes with a built-in vacuum gauge.

TECHNICAL SPECIFICATIONS

- Fast and effective drainage up to 15 microns
- Non-slip anti-vibration shock absorbers (silence and stability)
- Compact and well balanced, with a carrying handle
- Cooling with fins on the pump housing (optimum effectiveness and suction)
- Built-in vacuum gauge indicating min. 1.015 bar vacuum
- Check valve
- Gas ballast (eliminates humidity and condensable aspirated vapours)
- Big oil level monitoring light, drain cap and wide oil fill port
- Individually tested.

SPECIFICATIONS

Pump flow	95 l/min.
Number of stages	2 stages
Vacuum level	≤0.02 mbar (15 μ)
Input connectors with protective caps	1/4" + 1/2" male SAE
Motor	1,725 rpm
Power source	230 V - 50/60 Hz
Oil tank	≈ 590 ml
Size (mm)	381 x 169 x 300
Net weight	13.4 kg

The information in this article is the result of our studies and of our experience. It is given in good faith but cannot in any way constitute a guarantee from us, or mean that we accept liability, especially in the case of infringement of third parties or of failure by users of our products to abide with the relevant current regulations.

